

Product Data Sheet



HB-1112

LUBRAFILM

Oil Conditioner

DESCRIPTION:

- A highly viscous oil supplement which contains a shear-stable viscosity index improver to beef up any oil's film strength and the ability to keep engines cleaner.
- Contains a concentrate of Moly-G which will give armor-plate protection to any oil, including motor oils, gear oils and oils for other applications.

COMPOSITION:

Combines a highly refined viscosity index improver with a wide variety of stabilizing agents such as:

Acid-Neutriliizers
Anti-Wear Additives
Anti- Foam Agents

Oiliness Additives
Corrosion Inhibitors
Thermal Stability Agents

Lubrafilm helps any oil's ability to maintain proper viscosity under high heat conditions and contains components to reduce carbon and engine wear.

PERFORMANCE CHARACTERISTICS:

Controls Consumption
Removes Engine
Deposits Improves
Power
Neutralizes Harmful Engine
Acids Improves Compression
Prevents Excessive Wear

Reduces Blow-By
Reduces Lifter & Valve Noise Reduces
Frictional Drag
Seals Rings Better
Increases Oil Pressure
Reduces Piston Scuffing & Scoring

USES:

Especially recommended for use with all motor oils in:

Diesel Engines
Gasoline Engines Compressors
Air Cooled Engines
LPG Engines
Natural Gas Engines
Final Drives

Manual Transmissions
Differentials
Speed Reducers
Transfer Cases
Hydraulic Systems

TYPICAL APPLICATIONS:

Farm Tractors	Heavy Duty Trucks
Farm Implements	Stationary Engines
Power Plants	Excavators
Industrial Plants	Fork Lifts
Logging Equipment	Drilling Rigs
Boats	Oil Production Engines

SPECIFICATIONS:

Viscosity, SUS	
@100°F	25000
@210°F	2100
Viscosity, CsT	
@100°F	5000
@210°F	450
Specific Gravity	0.85
Color ASTM	Dark Green
Flash Point	140°F
Pour Point	-5°F
Acid Test	Excellent
1-H Test (M2C 1010 B)	Pass
Piston Skirt Varnish (10=clean)	9.0

